



ERTELALSOP

THE FIRST NAME IN LIQUID FILTRATION™

CONFIDENTIAL

SPECIFICATION SHEET

<u>Product Code:</u>	Filter Pads
<u>Grade Designation:</u>	M-053 XL Series
<u>Materials:</u>	Cellulose/ High Purity Celpure® DE
<u>Wet Strength Resin:</u>	Non-Hazardous, listed as safe under 21CFR 176.170
<u>Physical Properties:</u>	
<i>Surface:</i>	Mottled
<i>Color:</i>	White to Off-White
<i>Flowrate:</i>	1542.825 LPM/M ² 2250 GPH/ft ² Average (Water at Ambient in GPH/ft ²)
<i>Retention:</i>	15 microns nominal 15.0-20.0 microns effective range
<i>Thickness:</i>	4.1 mm (avg.)

- * Flowrate based on 70°F water flow through a 2 inch diameter filter at 10 PSI.
- * Retention based on retaining 98% of a given micron particle.
- * All components are listed in the CFR as generally recognized as safe for contact with food.

Celpure® is a registered Trademark of Advanced Minerals

ERTELALSOP • 132 FLATBUSH AVENUE • KINGSTON • NY • 12401
PHONE 845.331.4552 • FAX 845.853.1526 • ERTELALSOP.COM

SPECIFICATION SHEET