



ERTELALSOP

THE FIRST NAME IN LIQUID FILTRATION™

Confidential

SPECIFICATION SHEET

<u>Product Code:</u>	Biopak® Lenticular Filter Cartridge
<u>Grade Designation:</u>	16POY4M954P15NS
<u>Materials:</u>	Cellulose/ DE
<u>Wet Strength Resin:</u>	Non-Hazardous, listed as safe under 21CFR 176.170
<u>Physical Properties:</u>	
Surface:	Mottled
Color:	White to Off-White
Configuration:	15 Cells
<u>Performance Characteristics:</u>	
Flowrate:	30 GPM per Pak® Average 114 LPM per Pak® Average
Retention:	0.25 micron nominal
Filtration Area:	37.5 sq. ft. 3.5 sq. m.
<u>Components:</u>	
Gasket:	EPDM
Support Members:	Polypropylene

- * Flowrate based on 70°F (21°C) water flow through a 2 inch (50mm) diameter filter at 10 PSI.
- * Retention based on retaining 98% of a given micron particle.
- * All components are listed in the CFR as generally recognized as safe for contact with food.
- * Cells are constructed without polypropylene outer layer scrim

Note: Manufactured in accordance with ErtelAlsop Drug Master File located at the United States Food and Drug Administration Center for Drug Evaluation and Research