ERTELALSOP THE FIRST NAME IN LIQUID FILTRATION[™]

Confidential

SPECIFICATION SHEET

Product Code:	Zeta-Pak® Lenticular Filter Cartridge		
Grade Designation:	16SFY5M45416	16SFY5M45416	
<u>Materials</u> :	Cellulose/Diatomac	Cellulose/Diatomaceous Earth	
<u>Wet Strength Resin</u> :	Epichlorohydrin, No 21CFR 176.170	Epichlorohydrin, Non-Hazardous, listed as safe under 21CFR 176.170	
<u>Physical Properties</u> :			
	Surface:	Mottled	
	Color:	White to Off-White	
	Flowrate:	104-204 GPM per Pak® Average	
	Retention:	2.5 micron nominal	
	Configuration:	16 Cells	
	Filtration Area:	37 sq. ft.	
<u>Components:</u>			
	Gasket:	Buna-N	

Support Members:

Stainless Steel and Polypropylene Core

- * Flowrate based on 70°F water flow through a 2 inch diameter filter at 10 PSI.
- * Retention based on retaining 98% of a given micron particle.
- * All components are listed in the CFR as generally recognized as safe for contact with food

ERTELALSOP • 132 FLATBUSH AVENUE • KINGSTON • NY • 12401 PHONE 845.331.4552 • FAX 845.853.1526 • ERTELALSOP.COM