



ERTELALSOP

THE FIRST NAME IN LIQUID FILTRATION™

CONFIDENTIAL

SPECIFICATION SHEET

<u>Product Code:</u>	ZetaDri-Pak®
<u>Grade Designation:</u>	12SFX5M1009ZD
<u>Materials:</u>	Cellulose, Perlite, CMC water absorbing media, and Cellulose Filter Paper
<u>Wet Strength Resin:</u>	Non-Hazardous, listed as safe under 21CFR 176.170
<u>Physical Properties:</u>	
Surface:	Mottled
Color:	White to Off-White
Maximum Flowrate:	250-300 GPM per Pak® Average
Recommend Flowrate:	1 gallon per minute per square foot
Recommended Pressure:	30-35 PSID Maximum
Recommended Temperature:	190°F
Retention:	10 microns nominal
Configuration:	9 Cells
Filtration Area:	10.4 sq. ft.
Water Holding Capacity:	2485 ml minimum
Total Particulate:	1200 grams
Gasket:	Buna-N
Support Members:	Polypropylene and Stainless Steel
Dimensions (approx.):	11.3/8 inches diameter x 7 9/16 inches height
Packaging:	One Pak® per Polyethylene Heat Sealed Bag with desiccant 4 per carton, 23.75 "x11.5 x16", weight approximately 23 lbs.

- * Flowrate based on 70°F water flow through a 2 inch diameter filter at 10 PSI.
- * Retention based on retaining 98% of a given micron particle.
- * All components are listed in the CFR as generally recognized as safe for contact with food.